

Curva 45°

Codo 45° mango largo

Coude 45° embout long


Winkel 45°, lange Schweißenden

Fabricado por molde
Fabriqué par moulage

Fabricado mediante molde
Produziert mit Spritzgußverfahren




SDR17 PN10



* em desenvolvimento
* en fase de realización
* en cours de réalisation
* in Realisationsphase

dn	código	H [mm]	Z [mm]	Peso [Kg]
63	G4P063B	67	91	0,16
75	G4P075B	74	101	0,25
90	G4P090B	83	108	0,40
110	G4P110B	93	128	0,64
125	G4P125B	93	158	1,03
140	G4P140B	97	165	1,36
160	G4P160B	108	176	1,90
180	G4P180B	108	175	2,40
200	G4P200B	118	181	3,40
225	G4P225B	120	196	4,20
250	G4P250B	134	208	5,60
280	G4P280B	145	244	8,60
315	G4P315B	154	257	11,60
355	G4P355B	170	271	13,20
400	G4P400B	188	300	18,40
* 450	G4P450B	-	-	-
* 500	G4P500B	-	-	-

SDR11 PN16



* em desenvolvimento
* en fase de realización
* en cours de réalisation
* in Realisationsphase

dn	código	H [mm]	Z [mm]	Peso [Kg]
20	G4P020C	39	46	0,02
25	G4P025C	40	49	0,03
32	G4P032C	49	57	0,04
40	G4P040C	59	79	0,08
50	G4P050C	58	83	0,14
63	G4P063C	67	91	0,22
75	G4P075C	74	101	0,35
90	G4P090C	83	108	0,51
110	G4P110C	93	128	0,85
125	G4P125C	93	158	1,44
140	G4P140C	97	165	1,92
160	G4P160C	108	176	2,65
180	G4P180C	108	175	3,20
200	G4P200C	118	181	4,40
225	G4P225C	120	196	5,80
250	G4P250C	134	208	7,60
280	G4P280C	145	244	11,60
315	G4P315C	154	257	15,60
355	G4P355C	170	271	19,00
400	G4P400C	188	300	25,80
* 450	G4P450C	-	-	-
* 500	G4P500C	-	-	-

Curva 45°

Codo 45° mango largo

Coude 45° embout long


Winkel 45°, lange Schweißenden

Fabricado por molde
Fabriqué par moulage

Fabricado mediante molde
Produziert mit Spritzgußverfahren




SDR9 PN20



* em desenvolvimento
* en fase de realización
* en cours de réalisation
* in Realisationsphase

dn	código	H [mm]	Z [mm]	Peso [Kg]
63	G4P063G	67	91	0,25
75	G4P075G	74	101	0,40
90	G4P090G	83	108	0,60
110	G4P110G	93	128	1,08
125	G4P125G	93	158	1,86
140	G4P140G	97	165	2,40
160	G4P160G	108	176	3,42
180	G4P180G	108	175	4,16
200	G4P200G	118	181	5,66
225	G4P225G	120	196	6,80
250	G4P250G	134	208	9,88
280	G4P280G	145	244	13,50
315	G4P315G	154	257	20,00
355	G4P355G	170	271	23,20
400	G4P400G	188	300	31,40
* 450	G4P450G	-	-	-
* 500	G4P500G	-	-	-

SDR7,4 PN25



* em desenvolvimento
* en fase de realización
* en cours de réalisation
* in Realisationsphase

dn	código	H [mm]	Z [mm]	Peso [Kg]
40	G4P040H	59	79	0,10
50	G4P050H	58	83	0,18
63	G4P063H	67	91	0,29
75	G4P075H	74	101	0,46
90	G4P090H	83	108	0,69
110	G4P110H	93	128	1,21
125	G4P125H	93	158	2,00
140	G4P140H	97	165	2,59
160	G4P160H	108	176	3,60
180	G4P180H	108	175	4,40
200	G4P200H	118	181	6,00
225	G4P225H	120	196	8,00
250	G4P250H	134	208	10,20
280	G4P280H	145	244	15,60
315	G4P315H	154	257	21,00
355	G4P355H	170	271	25,80
400	G4P400H	188	300	35,60
* 450	G4P450H	-	-	-
* 500	G4P500H	-	-	-