


Tê 90° com redução
Te 90° reducida mango largo
Té réduit 90° embout long
T-Stück 90° reduziert, lange
Schweißenden

Fabricado por molde
Fabriqué par moulage

Fabricado mediante moldeo
Produziert mit Spritzgußverfahren



SDR17 PN10



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
90	50	TRP090050B	81	56	300	0,59
90	63	TRP090063B	81	70	300	0,63
110	50	TRP110050B	91	56	337	0,97
110	63	TRP110063B	91	70	337	1,01
110	90	TRP110090B	91	82	337	1,12
125	63	TRP125063B	91	70	356	1,38
125	90	TRP125090B	91	82	356	1,47
140	63	TRP140063B	96	70	387	1,87
140	90	TRP140090B	96	82	387	1,96
160	63	TRP160063B	104	70	424	2,53
160	90	TRP160090B	104	82	424	2,69
160	110	TRP160110B	104	90	424	2,75
160	125	TRP160125B	104	91	424	2,76
180	63	TRP180063B	107	64	450	4,36
180	90	TRP180090B	107	82	450	3,58
180	110	TRP180110B	107	90	450	4,45
180	125	TRP180125B	107	91	450	3,78
200	63	TRP200063B	117	82	500	4,46
200	90	TRP200090B	117	82	500	4,54
200	110	TRP200110B	117	90	500	4,62
200	125	TRP200125B	117	91	500	6,18
200	160	TRP200160B	117	105	500	4,90
200	180	TRP200180B	117	112	500	6,75
225	90	TRP225090B	120	84	539	6,48
225	125	TRP225125B	120	91	539	6,60
225	160	TRP225160B	120	104	539	6,80
225	180	TRP225180B	120	106	539	7,00
250	110	TRP250110B	131	92	595	9,60
250	125	TRP250125B	131	108	595	9,60
250	160	TRP250160B	131	105	595	10,00
250	180	TRP250180B	131	106	595	10,00
250	200	TRP250200B	131	117	595	12,20
280	110	TRP280110B	142	91	678	13,00
280	225	TRP280225B	142	120	678	-
315	110	TRP315110B	151	91	703	17,60
315	125	TRP315125B	151	105	703	19,10
315	160	TRP315160B	151	106	703	17,40
315	180	TRP315180B	151	116	703	17,75
315	200	TRP315200B	151	120	703	17,72
315	225	TRP315225B	151	121	703	18,29

Ver próxima página
Lisez la page suivante

Leer la página siguiente
Siehe nächste Seite

Tê 90° com redução

Te 90° reducida mango largo

Té réduit 90° embout long


T-Stück 90° reduziert, lange Schweißenden

Fabricado por molde
Fabriqué par moulage

Fabricado mediante moldeo
Produziert mit Spritzgußverfahren



SDR17 PN10



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
355	110	TRP355110B	176	89	687	20,65
355	160	TRP355160B	176	100	687	21,00
355	225	TRP355225B	176	125	687	21,25
355	250	TRP355250B	176	130	685	21,40
400	110	TRP400110B	190	88	750	28,80
400	160	TRP400160B	190	100	750	29,20
400	225	TRP400225B	190	125	750	29,40
450	160	TRP450160B	200	101	670	31,40
450	225	TRP450225B	200	125	795	39,80
450	315	TRP450315B	200	155	890	48,00
500	160	TRP500160B	218	100	720	39,60
500	250	TRP500250B	218	135	810	46,40
500	315	TRP500315B	218	162	925	58,20
560	250	TRP560250B	240	135	965	69,80
630	160	TRP630160B	255	100	800	65,50
630	250	TRP630250B	255	136	880	75,80
630	315	TRP630315B	255	157	1000	92,00


Tê 90° com redução
Te 90° reducida mango largo
Té réduit 90° embout long
T-Stück 90° reduziert, lange Schweißenden

Fabricado por molde
Fabriqué par moulage

Fabricado mediante molde
Produziert mit Spritzgußverfahren



SDR11 PN16



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
90	50	TRP090050C	81	56	300	0,79
90	63	TRP090063C	81	70	300	0,84
110	50	TRP110050C	91	56	337	1,30
110	63	TRP110063C	91	70	337	1,34
110	90	TRP110090C	91	82	337	1,50
125	63	TRP125063C	91	70	356	1,80
125	90	TRP125090C	91	82	358	1,98
140	63	TRP140063C	96	70	387	2,50
140	90	TRP140090C	96	82	387	2,62
160	63	TRP160063C	104	70	424	3,40
160	90	TRP160090C	104	82	424	3,57
160	110	TRP160110C	104	90	424	3,72
160	125	TRP160125C	104	91	424	3,82
180	63	TRP180063C	107	64	450	4,63
180	90	TRP180090C	107	82	450	4,80
180	110	TRP180110C	107	90	450	4,85
180	125	TRP180125C	107	91	450	5,04
200	63	TRP200063C	117	82	500	6,19
200	90	TRP200090C	117	82	500	6,32
200	110	TRP200110C	117	90	500	6,64
200	125	TRP200125C	117	91	500	6,52
200	160	TRP200160C	117	105	500	6,85
200	180	TRP200180C	117	112	500	7,15
225	90	TRP225090C	120	84	539	9,04
225	125	TRP225125C	120	91	539	9,20
225	160	TRP225160C	120	104	539	9,40
225	180	TRP225180C	120	106	539	9,60
250	110	TRP250110C	131	92	595	12,20
250	125	TRP250125C	131	108	595	12,40
250	160	TRP250160C	131	105	595	13,00
250	180	TRP250180C	131	106	595	13,00
250	200	TRP250200C	131	117	595	13,20
280	110	TRP280110C	142	91	678	17,60
280	225	TRP280225C	142	120	678	22,60

Ver próxima página
Lisez la page suivante

Leer la página siguiente
Siehe nächste Seite

Tê 90° com redução

Te 90° reducida mango largo

Té réduit 90° embout long


T-Stück 90° reduziert, lange Schweißenden

Fabricado por molde
Fabriqué par moulage

Fabricado mediante moldeo
Produziert mit Spritzgußverfahren




SDR11 PN16



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
315	110	TRP315110C	151	90	703	23,60
315	125	TRP315125C	151	95	703	24,00
315	160	TRP315160C	151	101	703	24,00
315	180	TRP315180C	151	107	703	24,30
315	200	TRP315200C	151	118	703	24,40
315	225	TRP315225C	151	121	703	24,37
355	110	TRP355110C	176	89	687	27,90
355	160	TRP355160C	176	100	687	28,18
355	225	TRP355225C	176	125	687	29,00
400	110	TRP400110C	190	88	750	38,20
400	160	TRP400160C	190	100	750	38,80
400	225	TRP400225C	190	125	750	40,00
450	160	TRP450160C	200	101	670	42,40
450	225	TRP450225C	200	125	795	52,80
450	315	TRP450315C	200	155	890	63,40
500	160	TRP500160C	218	100	720	54,80
500	250	TRP500250C	218	135	810	64,20
500	315	TRP500315C	218	162	925	77,80
560	250	TRP560250C	240	135	965	96,00
630	160	TRP630160C	255	100	800	95,00
630	250	TRP630250C	255	136	880	104,00
630	315	TRP630315C	255	157	1000	124,60

SDR9 PN20



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
110	90	TRP110090G	91	82	337	1,70
125	63	TRP125063G	91	70	356	2,10
125	90	TRP125090G	91	82	356	2,20
160	110	TRP160110G	104	90	424	3,72
225	110	TRP225110G	120	89	539	11,10
250	110	TRP250110G	131	92	595	14,40
250	160	TRP250160G	131	105	595	15,20
280	110	TRP280110G	142	91	678	20,78
280	225	TRP280225G	142	120	678	22,60
315	110	TRP315110G	151	90	703	28,40
315	160	TRP315160G	151	101	703	28,60
315	200	TRP315200G	151	118	703	30,71
315	225	TRP315225G	151	121	703	29,90
355	160	TRP355160G	176	100	687	35,80
400	110	TRP400110G	190	88	750	45,20
400	160	TRP400160G	190	100	750	44,60
400	225	TRP400225G	190	125	750	46,20
450	160	TRP450160G	200	101	670	49,40
450	225	TRP450225G	200	125	795	62,00
450	315	TRP450315G	200	155	890	74,50
560	250	TRP560250G	240	135	965	125,00

Tê 90° com redução

Te 90° reducida mango largo

Té réduit 90° embout long


T-Stück 90° reduziert, lange Schweißenden

Fabricado por molde
Fabriqué par moulage

Fabricado mediante moldeo
Produziert mit Spritzgußverfahren



SDR7,4 PN25



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
110	90	TRP110090H	91	82	337	2,10
125	63	TRP125063H	91	70	356	2,50
125	90	TRP125090H	91	82	356	2,70
200	180	TRP200180H	117	112	500	7,15
225	110	TRP225110H	120	89	539	13,30
250	160	TRP250160H	131	105	595	18,40
280	110	TRP280110H	142	91	678	24,90
280	225	TRP280225H	142	120	678	27,10
315	110	TRP315110H	151	90	703	34,10
315	160	TRP315160H	151	101	703	34,80
315	200	TRP315200H	151	118	703	36,80
315	225	TRP315225H	151	121	703	55,80
355	160	TRP355160H	176	100	687	37,54
400	110	TRP400110H	190	88	750	47,60
400	160	TRP400160H	190	100	750	51,80
400	225	TRP400225H	190	125	750	54,60
450	160	TRP450160H	200	101	670	59,30
450	225	TRP450225H	200	125	795	74,40
450	315	TRP450315H	200	155	890	89,40
560	250	TRP560250H	240	135	965	162,00