

## Tê longo 90° com redução

Te 90° reducida ensamblada mango largo

Té réduit assemble 90° embout long

Geschweißtes T-Stück 90° reduziert, lange Schweißenden




Fabricado por molde e soldadura a topo

Fabriqué par moulage et soudure bout à bout

Fabricado mediante moldeo y soldadura a tope

Produziert mit Spritzguß- und Stumpfschweißverfahren

**SDR17 PN10**



- Derivação com Tê Curto
- Mango largo en línea  
mango corto en lado reducido
- Embout long en ligne  
embout court en dérivation
- gradlinig lange Schweißenden,  
Abgang kurze Schweißenden

| dn  | dn1   | código     | H<br>[mm] | H1<br>[mm] | Z<br>[mm] | Peso<br>[Kg] |
|-----|-------|------------|-----------|------------|-----------|--------------|
| 110 | 75    | TRP110075B | 91        | 73         | 336       | -            |
| 125 | 75    | TRP125075B | 91        | 73         | 356       | -            |
| 125 | 110   | TRP125110B | 91        | 90         | 356       | -            |
| 140 | 110   | TRP140110B | 96        | 90         | 388       | -            |
| 140 | 125   | TRP140125B | 97        | 92         | 388       | -            |
| 160 | 140   | TRP160140B | 104       | 92         | 423       | -            |
| 180 | 140   | TRP180140B | 107       | 90         | 451       | -            |
| 180 | 160   | TRP180160B | 107       | 101        | 451       | -            |
| 200 | 140   | TRP200140B | 117       | 95         | 501       | -            |
| 225 | 110   | TRP225110B | 120       | 89         | 539       | -            |
| 225 | 200   | TRP225200B | 120       | 114        | 538       | -            |
| 250 | 225   | TRP250225B | 131       | 123        | 596       | -            |
| 280 | 200 • | TRP280200B | 142       | 50         | 678       | -            |
| 280 | 225 • | TRP280225B | 142       | 55         | 678       | -            |
| 280 | 250 • | TRP280250B | 142       | 63         | 678       | -            |
| 315 | 250   | TRP315250B | 151       | 63         | 702       | -            |
| 315 | 280 • | TRP315280B | 151       | 75         | 702       | -            |
| 355 | 280 • | TRP355280B | 168       | 75         | 800       | -            |
| 355 | 315 • | TRP355315B | 168       | 84         | 800       | -            |
| 400 | 280 • | TRP400280B | 180       | 75         | 880       | -            |
| 400 | 315 • | TRP400315B | 180       | 84         | 880       | -            |
| 400 | 355 • | TRP400355B | 180       | 93         | 880       | -            |
| 450 | 355 • | TRP450355B | 203       | 93         | 985       | -            |
| 450 | 400 • | TRP450400B | 203       | 98         | 985       | -            |
| 500 | 355 • | TRP500355B | 220       | 93         | 1090      | -            |
| 500 | 400 • | TRP500400B | 220       | 98         | 1090      | -            |
| 500 | 450 • | TRP500450B | 220       | 65         | 1090      | -            |
| 560 | 400 • | TRP560400B | 236       | 98         | 1200      | -            |
| 560 | 450 • | TRP560450B | 236       | 65         | 1200      | -            |
| 560 | 500 • | TRP560500B | 236       | 67         | 1200      | -            |
| 630 | 450 • | TRP630450B | 255       | 65         | 1310      | -            |
| 630 | 500 • | TRP630500B | 255       | 62         | 1310      | -            |
| 630 | 560 • | TRP630560B | 255       | 63         | 1310      | -            |

## Tê longo 90° com redução

Te 90° reducida ensamblada mango largo

Té réduit assemble 90° embout long

Geschweißtes T-Stück 90° reduziert, lange Schweißenden

Fabricado por molde e soldadura a topo


Fabricado mediante molde y soldadura a tope

Fabriqu   par moulage et soudure bout    bout

Produziert mit Spritzgu  - und Stumpfschwei  verfahren



**SDR11 PN16**



- Deriva  o com T   Curto
- Mango largo en linea  
mango corto en lado reducido
- Embout long en ligne  
embout court en d  rivation
- gradlinig lange Schwei  enden,  
Abgang kurze Schwei  enden

| dn  | dn1 | c  digo    | H<br>[mm] | H1<br>[mm] | Z<br>[mm] | Peso<br>[Kg] |
|-----|-----|------------|-----------|------------|-----------|--------------|
| 50  | 25  | TRP050025C | 57        | 45         | 180       | -            |
| 50  | 32  | TRP050032C | 57        | 45         | 180       | -            |
| 50  | 40  | TRP050040C | 57        | 50         | 180       | -            |
| 63  | 25  | TRP063025C | 68        | 43         | 229       | -            |
| 63  | 32  | TRP063032C | 68        | 45         | 229       | -            |
| 63  | 40  | TRP063040C | 68        | 50         | 229       | -            |
| 63  | 50  | TRP063050C | 68        | 55         | 229       | -            |
| 75  | 32  | TRP075032C | 72        | 45         | 256       | -            |
| 75  | 40  | TRP075040C | 72        | 50         | 256       | -            |
| 75  | 50  | TRP075050C | 72        | 50         | 256       | -            |
| 75  | 63  | TRP075063C | 72        | 64         | 256       | -            |
| 90  | 75  | TRP090075C | 81        | 73         | 303       | -            |
| 110 | 75  | TRP110075C | 91        | 73         | 336       | -            |
| 125 | 75  | TRP125075C | 91        | 73         | 356       | -            |
| 125 | 110 | TRP125110C | 91        | 90         | 356       | -            |
| 140 | 110 | TRP140110C | 96        | 90         | 388       | -            |
| 140 | 125 | TRP140125C | 97        | 92         | 388       | -            |
| 160 | 140 | TRP160140C | 104       | 90         | 423       | -            |
| 180 | 140 | TRP180140C | 107       | 90         | 451       | -            |
| 180 | 160 | TRP180160C | 107       | 101        | 451       | -            |
| 200 | 140 | TRP200140C | 117       | 95         | 501       | -            |
| 225 | 110 | TRP225110C | 120       | 89         | 539       | -            |
| 225 | 200 | TRP225200C | 120       | 114        | 538       | -            |
| 250 | 225 | TRP250225C | 131       | 123        | 596       | -            |
| 280 | 110 | TRP280110C | 142       | 91         | 678       | -            |
| 280 | 200 | TRP280200C | 142       | 50         | 678       | -            |
| 280 | 225 | TRP280225C | 142       | 68         | 678       | -            |
| 280 | 250 | TRP280250C | 142       | 63         | 678       | -            |
| 315 | 250 | TRP315250C | 151       | 63         | 702       | -            |
| 315 | 280 | TRP315280C | 151       | 75         | 702       | -            |
| 355 | 250 | TRP355250C | 168       | 63         | 800       | -            |
| 355 | 280 | TRP355280C | 168       | 75         | 800       | -            |
| 355 | 315 | TRP355315C | 168       | 84         | 800       | -            |
| 400 | 280 | TRP400280C | 180       | 75         | 880       | -            |
| 400 | 315 | TRP400315C | 180       | 84         | 880       | -            |
| 400 | 355 | TRP400355C | 180       | 93         | 880       | -            |
| 450 | 355 | TRP450355C | 203       | 93         | 985       | -            |
| 450 | 400 | TRP450400C | 203       | 98         | 985       | -            |
| 500 | 355 | TRP500355C | 220       | 93         | 1090      | -            |
| 500 | 400 | TRP500400C | 220       | 98         | 1090      | -            |
| 500 | 450 | TRP500450C | 220       | 65         | 1090      | -            |
| 560 | 400 | TRP560400C | 236       | 98         | 1200      | -            |
| 560 | 450 | TRP560450C | 236       | 65         | 1200      | -            |
| 560 | 500 | TRP560500C | 236       | 67         | 1200      | -            |
| 630 | 450 | TRP630450C | 255       | 65         | 1310      | -            |
| 630 | 500 | TRP630500C | 255       | 62         | 1310      | -            |
| 630 | 560 | TRP630560C | 255       | 63         | 1310      | -            |

## Tê longo 90° com redução

Te 90° reducida ensemblada mango largo

Té réduit assemble 90° embout long

Geschweißtes T-Stück 90° reduziert, lange Schweißenden

Fabricado por molde e soldadura a topo


Fabriqu  par moulage et soudure bout   bout

Fabricado mediante molde y soldadura a tope

Produziert mit Spritzgu - und Stumpfschwei verfahren



### SDR9 PN20



- Deriva  o com T  Curto
- Mango largo en linea  
mango corto en lado reducido
- Embout long en ligne  
embout court en d rivation
- gradlinig lange Schwei enden,  
Abgang kurze Schwei enden

| dn  | dn1   | c digo     | H<br>[mm] | H1<br>[mm] | Z<br>[mm] | Peso<br>[Kg] |
|-----|-------|------------|-----------|------------|-----------|--------------|
| 110 | 50    | TRP110050G | 91        | 55         | 336       | -            |
| 110 | 63    | TRP110063G | 91        | 64         | 336       | -            |
| 110 | 75    | TRP110075G | 91        | 73         | 336       | -            |
| 110 | 90    | TRP110090G | 91        | 82         | 336       | -            |
| 125 | 63    | TRP125063G | 87        | 67         | 356       | -            |
| 125 | 75    | TRP125075G | 87        | 73         | 356       | -            |
| 125 | 90    | TRP125090G | 87        | 82         | 356       | -            |
| 125 | 110   | TRP125110G | 87        | 90         | 356       | -            |
| 140 | 90    | TRP140090G | 96        | 83         | 388       | -            |
| 140 | 110   | TRP140110G | 96        | 90         | 388       | -            |
| 140 | 125   | TRP140125G | 96        | 92         | 388       | -            |
| 160 | 90    | TRP160090G | 104       | 82         | 423       | -            |
| 160 | 110   | TRP160110G | 104       | 90         | 423       | -            |
| 160 | 125   | TRP160125G | 104       | 92         | 423       | -            |
| 160 | 140   | TRP160140G | 104       | 90         | 423       | -            |
| 180 | 125   | TRP180125G | 107       | 92         | 451       | -            |
| 180 | 140   | TRP180140G | 107       | 90         | 451       | -            |
| 180 | 160   | TRP180160G | 107       | 101        | 451       | -            |
| 200 | 140   | TRP200140G | 117       | 95         | 501       | -            |
| 200 | 180   | TRP200180G | 117       | 106        | 501       | -            |
| 225 | 200   | TRP225200G | 120       | 118        | 538       | -            |
| 250 | 200   | TRP250200G | 131       | 117        | 595       | -            |
| 250 | 225   | TRP250225G | 131       | 68         | 596       | -            |
| 280 | 200 • | TRP280200G | 142       | 50         | 678       | -            |
| 280 | 225 • | TRP280225G | 142       | 55         | 678       | -            |
| 280 | 250 • | TRP280250G | 142       | 63         | 678       | -            |
| 315 | 225 • | TRP315225G | 151       | 55         | 702       | -            |
| 315 | 250 • | TRP315250G | 151       | 63         | 702       | -            |
| 315 | 280 • | TRP315280G | 151       | 75         | 702       | -            |
| 400 | 280 • | TRP400280G | 180       | 75         | 880       | -            |
| 400 | 315 • | TRP400315G | 180       | 84         | 880       | -            |
| 400 | 355 • | TRP400355G | 180       | 93         | 880       | -            |
| 450 | 355 • | TRP450355G | 203       | 93         | 985       | -            |
| 450 | 400 • | TRP450400G | 203       | 98         | 985       | -            |
| 500 | 355 • | TRP500355G | 220       | 93         | 1090      | -            |
| 500 | 450 • | TRP500450G | 220       | 65         | 1090      | -            |
| 560 | 400 • | TRP560400G | 236       | 98         | 1200      | -            |
| 630 | 500 • | TRP630500G | 255       | 61         | 1310      | -            |

Tê longo 90° com redução

Te 90° reducida ensemblada mango largo

Té réduit assemble 90° embout long

Geschweißtes T-Stück 90° reduziert, lange Schweißenden

Fabricado por molde e soldadura a topo


Fabriqu   par moulage et soudure bout    bout

Fabricado mediante molde y soldadura a tope

Produziert mit Spritzgu  - und Stumpfschwei  verfahren



**SDR7,4 PN25**



| dn  | dn1 | c  digo    | H<br>[mm] | H1<br>[mm] | Z<br>[mm] | Peso<br>[Kg] |
|-----|-----|------------|-----------|------------|-----------|--------------|
| 50  | 25  | TRP050025H | 57        | 45         | 180       | -            |
| 50  | 32  | TRP050032H | 57        | 45         | 180       | -            |
| 50  | 40  | TRP050040H | 57        | 50         | 180       | -            |
| 63  | 25  | TRP063025H | 68        | 43         | 229       | -            |
| 63  | 32  | TRP063032H | 68        | 45         | 229       | -            |
| 63  | 40  | TRP063040H | 68        | 50         | 229       | -            |
| 63  | 50  | TRP063050H | 68        | 55         | 229       | -            |
| 75  | 32  | TRP075032H | 72        | 45         | 256       | -            |
| 75  | 40  | TRP075040H | 72        | 50         | 256       | -            |
| 75  | 50  | TRP075050H | 72        | 50         | 256       | -            |
| 75  | 63  | TRP075063H | 72        | 64         | 256       | -            |
| 90  | 50  | TRP090050H | 81        | 56         | 303       | -            |
| 90  | 63  | TRP090063H | 81        | 64         | 303       | -            |
| 90  | 75  | TRP090075H | 81        | 64         | 303       | -            |
| 110 | 50  | TRP110050H | 91        | 55         | 336       | -            |
| 110 | 63  | TRP110063H | 91        | 64         | 336       | -            |
| 110 | 75  | TRP110075H | 91        | 73         | 336       | -            |
| 110 | 90  | TRP110090H | 91        | 82         | 336       | -            |
| 125 | 63  | TRP125063H | 87        | 67         | 356       | -            |
| 125 | 75  | TRP125075H | 87        | 73         | 356       | -            |
| 125 | 90  | TRP125090H | 87        | 82         | 356       | -            |
| 125 | 110 | TRP125110H | 87        | 90         | 356       | -            |
| 140 | 90  | TRP140090H | 96        | 83         | 390       | -            |
| 140 | 110 | TRP140110H | 96        | 90         | 390       | -            |
| 140 | 125 | TRP140125H | 96        | 92         | 390       | -            |
| 160 | 90  | TRP160090H | 104       | 82         | 423       | -            |
| 160 | 110 | TRP160110H | 104       | 90         | 423       | -            |
| 160 | 125 | TRP160125H | 104       | 92         | 423       | -            |
| 160 | 140 | TRP160140H | 104       | 90         | 423       | -            |
| 180 | 125 | TRP180125H | 107       | 92         | 451       | -            |
| 180 | 140 | TRP180140H | 107       | 90         | 451       | -            |

Ver pr  xima p  gina  
Lisez la page suivante

Leer la p  gina siguiente  
Siehe n  chste Seite

## Tê longo 90° com redução

Te 90° reducida ensamblada mango largo

Té réduit assemble 90° embout long

Geschweißtes T-Stück 90° reduziert, lange Schweißenden

Fabricado por molde e soldadura a topo


Fabrique par moulage et soudure bout à bout

Fabricado mediante molde y soldadura a tope

Produziert mit Spritzguß- und Stumpfschweißverfahren



**SDR7,4 PN25**



- Derivação com Tê Curto
- Mango largo en linea  
mango corto en lado reducido
- Embout long en ligne  
embout court en dérivation
- gradlinig lange Schweißenden,  
Abgang kurze Schweißenden

| dn  | dn1   | código     | H<br>[mm] | H1<br>[mm] | Z<br>[mm] | Peso<br>[Kg] |
|-----|-------|------------|-----------|------------|-----------|--------------|
| 180 | 160   | TRP180160H | 107       | 101        | 451       | -            |
| 200 | 140   | TRP200140H | 117       | 95         | 501       | -            |
| 200 | 180   | TRP200180H | 117       | 106        | 501       | -            |
| 225 | 200   | TRP225200H | 120       | 118        | 538       | -            |
| 250 | 200 • | TRP250200H | 131       | 58         | 596       | -            |
| 250 | 225 • | TRP250225H | 131       | 68         | 596       | -            |
| 280 | 200 • | TRP280200H | 142       | 50         | 678       | -            |
| 280 | 225 • | TRP280225H | 142       | 55         | 678       | -            |
| 280 | 250 • | TRP280250H | 142       | 63         | 678       | -            |
| 315 | 225 • | TRP315225H | 151       | 55         | 702       | -            |
| 315 | 250 • | TRP315250H | 151       | 63         | 702       | -            |
| 315 | 280 • | TRP315280H | 151       | 75         | 702       | -            |
| 400 | 280 • | TRP400280H | 180       | 75         | 880       | -            |
| 400 | 315 • | TRP400315H | 180       | 84         | 880       | -            |
| 400 | 355 • | TRP400355H | 180       | 93         | 880       | -            |
| 450 | 355 • | TRP450355H | 203       | 93         | 985       | -            |
| 450 | 400 • | TRP450400H | 203       | 98         | 985       | -            |
| 500 | 450 • | TRP500450H | 220       | 65         | 1090      | -            |
| 560 | 400 • | TRP560400H | 236       | 98         | 1200      | -            |
| 630 | 500 • | TRP630500H | 255       | 61         | 1310      | -            |